



WESEM



additional lamps

134 x 64

0630, 0632

*halogen H3
fog and driving lights*

designed for cars Lublin: 2, 3

universal application

installed upright or upside down

Construction and parameters

Application

To be mounted at the front of the car or truck.

Designed especially for the cars with small recesses in the bumper.

General information

E8 approval mark refers to halogen driving lights and E20 mark refers to halogen fog lights.

Construction

- metal reflector
- black plastic housing
- glass lens
- mounting bracket with screws
- cable terminated with F/6,3 and A-2,5 terminals
- bulb (option)

Additional features

Mounting and adjustment system permits easy and accurate 3D aiming.

Bulbs

Fit bulbs type:

H3 12V 55W or H3 24V 70W

Parameters

The driving light reference mark, which specifies the light's maximum luminous intensity is 12.5 (it is about 60 lx within distance of 25 m).

Mounting methods

They can be installed on a vehicle in an upright or upside-down position.

Dedicated application

A-Lublin II (from 1997),
Lublin III (from 1999)

Cat. number	Zelmot Catal. No.	Homologation code	Light function		Lens colour	clear	Accessories	bulb H3 12V	bulb H3 24V	cable 0,15 m	cable 0,5 m	Application		Mounting		Mounting method		Side	right / left	Packaging / pc	carton box
			fog light	driving light								universal	dedicated	bracket	spoiler / recess	installed vertically up	suspended				
0630.45600	0630.4.000.2	630	*			*						*		*				*	*	*	1
0630.45601	0630.4.000.1	630	*			*		*				*		*				*	*	*	1
0630.45610	0630.5.000.2	630	*			*				*		*	A	*				*	*	*	1
0630.45611	0630.5.000.1	630	*			*	*			*		*	A	*			*	*	*	*	1
0632.45700	0632.1.000.2	632		*		*			*			*		*				*	*	*	1
0632.45701	0632.1.000.1	632		*		*	*		*			*		*				*	*	*	1

Homologation code means identifier of certification number.

